

| ASME B16.25 | | | | |
|-------------|----------------|-------|-------|--------|
| Za cev | Redukcioni deo | | | |
| | A | C | F | Kg/kom |
| 1/8" | 16,0 | 13,7 | 10,3 | 1,73 |
| 1/4" | 16,0 | 13,7 | 13,7 | 2,24 |
| 3/8" | 19,0 | 17,1 | 17,1 | 2,31 |
| 1/2" | 19,0 | 21,3 | 21,3 | 2,77 |
| 3/4" | 22,0 | 26,7 | 26,7 | 2,87 |
| 1" | 27,0 | 33,4 | 33,4 | 3,38 |
| 1 1/4" | 32,0 | 42,2 | 42,2 | 3,56 |
| 1 1/2" | 33,0 | 48,3 | 48,3 | 3,68 |
| 2" | 38,0 | 60,3 | 60,3 | 3,91 |
| 2 1/2" | 41,0 | 73 | 73,0 | 5,16 |
| 3" | 44,0 | 88,9 | 88,9 | 5,49 |
| 3 1/2" | 48,0 | 101,6 | 101,6 | 5,74 |
| 4" | 51,0 | 114,3 | 114,3 | 6,02 |
| 5" | 57,0 | 141,3 | 141,3 | 6,55 |
| 6" | 78,0 | 168,3 | 168,3 | 7,11 |
| 8" | 99,0 | 219,3 | 219,3 | 8,11 |
| 10" | 94,0 | 273,1 | 273,1 | 9,27 |
| 12" | 103,0 | 323,9 | 323,9 | 9,53 |
| 14" | 100,0 | 355,6 | 355,6 | 9,53 |
| 16" | 106,0 | 406,4 | 406,4 | 9,53 |
| 18" | 111,0 | 457,2 | 457,2 | 9,53 |
| 20" | 119,0 | 508 | 508,0 | 9,53 |
| 24" | 140,0 | 609,6 | 609,6 | 9,53 |